



Reticle 
Catalogue

Thermal Imaging Riflescope

THERMION 2 XP50
PRO

Non-scalable reticles

The values of the non-scalable reticles are correct in the following cases:

- when the magnification of the scope is set to minimum
- when "picture in picture" is activated



D50i



C50i



X54i



H50i



X50i



T54



M58i



X51 Fi-300



M56Fi (Mil-Dot)



M57Fi (Mil-Dot)


Scalable reticles

Reticle parameters apply to all magnifications



D50i

Reticle parameters
(apply to all magnifications)





	MOA	cm @ 100 m
Section A	5.1	14.9
Section B	5.1	14.9
Section C	0.7	2.1

Thermal Imaging Riflescope

THERMION 2 XP50 PRO

C50i

Reticle parameters
(apply to all magnifications)



	MOA	cm @ 100 m
Section A	5.1	14.9
Section B	5.1	14.9
Section C	0.7	2.1
Section D	68.8	200



Thermal Imaging Riflescope

THERMION 2 XP50 PRO

[↑ TO CONTENT](#)

X54i

Reticle parameters
(apply to all magnifications)




	MOA	cm @ 100 m
Section A	5.1	14.9
Section B	5.1	14.9
Section C	0.7	2.1
Section D	68.8	200

Thermal Imaging Riflescope


THERMION 2 XP50 PRO

[↑ TO CONTENT](#)

H50i



Reticle parameters
(apply to all magnifications)




	MOA	cm @ 100 m
Section A	5.1	14.9
Section B	5.1	14.9
Section C	0.7	2.1
Section D	20	58
Section E	20	58
Section F	63.5	185
Section G	219.8	640

Thermal Imaging Riflescope


THERMION 2 XP50 PRO

[↑ TO CONTENT](#)

X50i



Reticle parameters
(apply to all magnifications)




	MOA	cm @ 100 m
Section A	5.1	14.9
Section B	5.1	14.9
Section C	0.7	2.1
Section D	34.4	100
Section E	68.8	200
Section F	2.1	6.1
Section G	195	568

Thermal Imaging Riflescope


THERMION 2 XP50 PRO

[↑ TO CONTENT](#)

T54



Reticle parameters
(apply to all magnifications)




	MOA	cm @ 100 m
Section A	68.8	200
Section B	195	567
Section C	232	676
Section D	5.1	15


Thermal Imaging Riflescope

THERMION 2 XP50 PRO

M58i



Reticle parameters
(apply to all magnifications)



	MOA	cm @ 100 m
Section A	0.7	2.1 on 2x magnification
Section B	3.5	10 (1 mil) on 16x magnification
Section C	3.5	10 (1 mil) on 8x magnification
Section D	3.5	10 (1 mil) on 16x magnification
Section a		1 mil (10 cm @ 100 m) on 2x magnification
Section b		1 mil (10 cm @ 100 m) on 4x magnification
Section c		1 mil (10 cm @ 100 m) on 8x magnification
Section d		1 mil (10 cm @ 100 m) on 12x magnification
Section e		1 mil (10 cm @ 100 m) on 16x magnification


Thermal Imaging Riflescope

THERMION 2 XP50 PRO


[↑ TO CONTENT](#)

X51 Fi-300

SCALABLE



Reticle parameters
(apply to all magnifications)




	200 m	300 m
Section A	15 cm (fox body)	23 cm (roe deer body)
Section B	23 cm (roe deer body)	35 cm (wild boar body)
Section C	35 cm (wild boar body)	50 cm (deer body)
Section D	—	15 cm (fox body)


Thermal Imaging Riflescope

THERMION 2 XP50 PRO

[↑ TO CONTENT](#)



Reticle parameters
(apply to all magnifications)




	MOA	CM @ 100 M
Section A	3.5	10 (1 MIL)
Section B	3.5	10 (1 MIL)
Section C	0.86	2.5 (0.25 MIL)


Thermal Imaging Riflescope

THERMION 2 XP50 PRO

↑ TO CONTENT



Reticle parameters
(apply to all magnifications)



	MOA	CM @ 100 M
Section A	3.5	10 (1 MIL)
Section B	3.5	10 (1 MIL)
Section C	0.86	2.5 (0.25 MIL)

Thermal Imaging Riflescope

THERMION 2 XP50 PRO

[↑ TO CONTENT](#)



www.pulsar-vision.com